

EASY ORDER CHECKLIST



THE NATCHEZ STREET NAME SYSTEM

STEP 1

Choose a 3" OD Post Style



Smooth Finish Steel Post



Fluted Finish Aluminum Post

STEP 2

Choose Post Lengths & Qty's:

QTY: ___ 10' QTY: ___ 12' QTY: ___ 14'

MUTCD Guidance: When not using a breakaway anchor, posts should be embedded in concrete and buried 2ft in the ground. Proper Mounting height is 7ft foot from the bottom of sign to the road surface.

STEP 3

Choose Breakaway Systems & Qty's:

QTY: ___ Non-Breakaway Surface Mount Welded Plate
 QTY: ___ V-Loc: Soft Soil
 QTY: ___ V-Loc: Existing Concrete
 QTY: ___ V-Loc: New Concrete
 QTY: ___ Non-Breakaway Anchor Plate None


STEP 4

Choose Base Style for ALL Posts:

9993-27" SB-33-24" 8397-8.5" None

NOTE: Posts must be ordered separately.



◆ **8397: 8½" Tall Base:**
 Attach directly to a 3" round post with 3 set screws, included.  OPOZBR38397ABK



◆ **9993: 27" Tall Aluminum Base**
 Easy to install. This base clam-shells around new or existing poles and lock together using steel fasteners. Tightens to the post with 2 set screws, included.

◆ **SB-33: 24" Tall Aluminum Base**
 Easy to install. This base clam-shells around new or existing poles and lock together using steel fasteners.

OPOZBR39993BK OPOZBR35B33BK

STEP 5

Choose Style for ALL Post Top Finals:



Pineapple



Spear



Ball

OPOZFR3657MDBK

OPOZFR39516MDBK

OPOZFR3FINB3BK

◆ 3 black set screws to attach to the post are included.
 The allen wrench to tighten set screws is NOT included.

STEP 6

Choose a Sign Blade Size:

QTY: ___ 30" Sign Blades QTY: ___ 36" Sign Blades

◆ For use on low volume roads with Speed Limits 25 MPH or less



◆ 4" Letter Height minimum

◆ Use with Sign Arm or #800 Cantilever Wing Brackets

◆ For use on higher volume, conventional roads with Speed Limits over 25 MPH



◆ 6" Letter Height minimum

◆ Use with Sign Arm or #800 Cantilever Wing Brackets

Sizes follow the guidelines in the MUTCD (Manual on Uniform Traffic Control Devices), the national standard used for all roads, including private roads open to public travel.

STEP 7

Choose a Sign Bracket:

#800 Cantilever Wing



OIS2ZUNCT800BK
 24" Long

Sign Arm



OIS2ZUNSA

NOTE: A bent lip sign style is required for use with a Sign Arm Bracket. A no lip sign style is required for use with Cantilever Wing Bracket.

EASY ORDER CHECKLIST

The Natchez Street Name System is the simplistic, sleek and modern version of our original Oxford System. Utilize our modular components including 3" posts, post bases, sleek sign arm brackets or metro wing brackets and finials to create your own modern system. Powder coated semi-gloss black for an elegant look.



NOTE: All Signs come standard with High Intensity Prismatic (HIP) sheeting and as a Flat, Double-Faced Sign Blade, unless otherwise requested. **Please E-Mail this form, along with a typed list of street name signs desired, to sales@cpcsigns.com**
Example: 30" Sign Blades: Qty (2) Main St, Qty (4) Henderson Ct --- 36" Sign Blades: Qty (1) Clarksdale Rd, Qty (3) Custom Ave

STEP 8 Choose a Sign Style:

Standard **Standard Dr**

- bent lip
- no lip

Deluxe (Routed Sign)



STEP 9 Choose Sign Color Scheme:

- White on Green
- White on Blue
- White on Brown
- Black on White
- White on Black
- Other/Custom



MUTCD Guidance: Acceptable alternative background colors to Green are Blue, Brown or White. The legend shall be White, except for Black on White signs. Custom colors require adequate contrast.

STEP 10 Choose Configuration:

- Offset
- Offset/Inverted



STEP 11 Choose Sign Border Style:

- NONE
- Edge - Use on dark backgrounds
- Inset - Use on white backgrounds

MUTCD Guidance: Borders are optional, but if used, must be the same color as the letters.

STEP 12 Choose Font/Prefix/Suffix:

Letter Font

- Highway Gothic
- Custom Font

MUTCD Guidance: Street Name Signs shall be composed of a combination of upper and lower case letters.

Prefix: Full Size Half Size

Suffix: Half Size Full Size

CPC Standard

MUTCD Guidance: Prefix/Suffix Height may be smaller than the height of the primary copy and may be abbreviated. No punctuation is to be used.

STEP 13 Choose Traffic Signs & Qtys:

QTY: ___ 30" STOP QTY: ___ 36" Yield

QTY: ___ 30" Warning

QTY: ___ Other NONE



STEP 14 Choose Traffic Sign Backer Style:

- NONE
- Plate
- Frame
- Laminate



STEP 15 Choose Traffic Sign Hardware:

- U-Bolt Clamp
- NONE

(Set of 2) for 3" O.D. Post
OTSBZR3UBCLAMP3BK

